

	FUELING EQUIPMENT	Date:
	TOOLBOX / TAILGATE TALK	Presenter:

FUELING/DIESELING EQUIP. SAFE WORK PRACTICES

Fueling Equipment

While fueling equipment, the following procedures must be followed.

- Turn off vehicle ignition.
- Place vehicle in gear and engage brake. (if applicable)
- No smoking, open flames or other sources of ignition within 7.5 metres (25') of fuel.
- Note the location of fire extinguishers.
- Do not cause spillage of any amount.
- Do not leave nozzle unattended while fueling.
- Do not fully top up fuel tank.
- Put nozzle and hose back in the proper place.



Dieseling Equipment

Our company firmly believes in protecting the environment from materials that would endanger wildlife. To prevent polluting the groundwater and streams of our communities, the following safe work practices must be followed:

1. Report all leaks as soon as possible. If a vehicle or piece of machinery leaks diesel, contain the spill using proper spill control procedures.
2. Never diesel equipment near waterways.
3. Never diesel on asphalt.
4. Never diesel where a source of ignition is present.
5. Guard against over-dieseling.



PRINT NAME IN FULL	SIGNATURE
1.	
2.	
3.	
4.	
5.	
6.	
7.	
8.	
9.	
10.	
11.	
12.	
13.	
14.	
15.	
16.	
17.	
18.	
19.	
20.	
21.	