

2025 Action Plan for Use of Liquid Anti-Stripping Asphalt Additives on Nova Scotia Department of Public Works Hot and Warm Mix Paving Projects

Table of Contents

- 1. Introduction**
- 2. Background**
- 3. Nova Scotia Department of Public Works (NSDPW) Contract Specifications**
- 4. Review of New Anti-Stripping Asphalt Additives**
- 5. Approval of Liquid Anti-Stripping Additives**
 - For All Products
 - For Formulations Containing Amines
- 6. List of “Acceptable” Anti-Stripping Asphalt Hot Mix and Warm Mix Additives for 2025 NSDPW Projects**
 - Additives that do NOT contain active amine compounds
 - Additives that DO contain active amine compounds
- 7. Approval of Asphalt Cement Suppliers**
- 8. Cooperation with Concerned Parties**
- 9. 2025 Action Plan**
- 10. Pre-Construction Meeting**
- 11. Site-Specific Safety Plan and Project-Specific Safe Work Practices**
- 12. Worker Information Sessions**
- 13. Protective Clothing and Personal Protective Equipment**
- 14. Removing Asphalt Containing Liquid Anti-Stripping Additive from Skin**
- 15. Respiratory Protective Equipment (RPE)**
- 16. Contingency System**
- 17. Protecting the Sensitive Worker**
- 18. Further Information**
- 19. Resource Materials**

1. Introduction

“Stripping” of asphalt pavement is a failure of the bond between the asphalt binder and the aggregate which allows the surface of the paved road to deteriorate by having individual pieces of aggregate break free leading to a general erosion of the surface over the affected area. Laboratory tests have been developed to help identify asphalt pavement mixes that are susceptible to stripping. There are a number of options possible when a pavement mix is identified by the laboratory as having failed the stripping tests.

One option is to add a liquid anti-stripping asphalt additive to the liquid asphalt binder to modify its binding properties and keep it firmly adherent to the aggregate, thus preventing or reducing the stripping problem. Only liquid anti-stripping asphalt additives which have passed the NSDPW toxicological and health criteria for inclusion on the List of “Acceptable” Anti-stripping Asphalt Hot Mix and Warm Mix Additives for 2025 NSDPW Projects are permitted to be used on NSDPW paving projects.

Please note that for 2025, amine-based liquid anti-stripping additives are no longer permitted to be used on Rural Impact Mitigation (RIM) projects.

This Action Plan APPLIES to hot and warm mix asphalt pavement formulations to which liquid anti-stripping asphalt additives have been added.

There are also a growing number of asphalt additives that are not used for anti-stripping purposes but may be added for other reasons. This is particularly true for warm mix formulations. Precautions not included in this plan may be required for these additives.

2. Background

Before 1994, liquid anti-stripping (LAS) asphalt additives were not used on Nova Scotia government highway paving projects. In 1994, amine-based LAS additives were used experimentally on three projects to improve the bonding of the liquid asphalt cement to the aggregate in order to prevent stripping of the road surface. On these projects a number of workers experienced severe eye, nose and throat irritation; nausea; vomiting; dizziness and headaches. When progressively aggressive attempts to control these problems with personal protective equipment were unsuccessful, the use of the LAS asphalt additives was discontinued for the remainder of the paving season while solutions were found to the problem of workers experiencing adverse health effects.

Research identified components in the amine-based LAS asphalt additives used in 1994 which were consistent with the health effects experienced by the workers. Alternative products were investigated and a list of “Acceptable” products with reduced health effects was developed for use on future projects. These products were chosen because they had low vapour, low odour, low irritation potential and no long-term health effects.

Over time, industry research has resulted in new generations of amine-based LAS products which have even fewer and less severe health effects, and a number of LAS products that are not based on amine chemistry. These newer products have progressively replaced the earlier products.

Working with all the stakeholders, the Department also developed an Action Plan to overcome any residual health and safety problems associated with the use of the newer LAS additives on the list of “Acceptable” products. The selection of new products and the development of the LAS Action Plan resolved many of the issues. Further experience with the use of LAS additives has led to improved procedures to eliminate or reduce exposure.

Changes in paving technology have also resulted in warm mix processes as well as hot mix processes, with new additives associated with the warm mix processes and lower risk for workers on these projects.

Each year since 1995, the Action Plan has been updated as experience in working successfully with liquid anti-stripping additives increased, and in the light of any new problems experienced. The Action Plans have included revised departmental Contract Specifications, contractor planning and Worker Information Sessions, and have included a series of progressive actions to be taken to protect affected workers.

Protective measures now include product selection, modification of equipment, safe work practices, restricting paving operations during damp or wet conditions, use of personal protective equipment when required, and relocating affected workers to work areas where there is less exposure to the additive. Finally, when necessary, affected workers must be moved to another project where there is no exposure to the additive.

Historically, symptoms appeared to be more likely to develop when working in the smoke from the hot mix plant or after a period of several days of exposure on paving operations. Symptoms occurred particularly after exposure during wet conditions, when the steam rising from the pavement carried traces of the amine additive into the air breathed by workers.

During the 1995 to 2012 paving seasons, most of the projects proceeded without incident. Only a few workers reported mild symptoms such as dry lips, dry mouth, coughing spells, nausea, feeling faint, a feeling of burning in throat or chest, or headaches. Usually, these symptoms would disappear after a few minutes spent in uncontaminated air. In the very few more severe cases, symptoms disappeared within a couple of days after exposure to the amine-based liquid anti-stripping additive stopped. Investigating how these workers were exposed, it was found that poor layout of the hot mix plant site and worker exposure to the smoke from the stack or fume from the hot mix were the most common causes.

In the 2008, 2009, 2010 and the 2013 to 2023 paving seasons, no adverse health effects were reported to the Department from any of the projects using liquid anti-stripping additives. There have not been any incidents of health effects reported since 2012, which demonstrates that careful selection of materials and attention to proper precautions during use can successfully control the potential adverse health effects.

However, there was one RIM (Rural Impact Mitigation) project in 2024 that experienced difficulties in using an amine-based liquid anti-stripping additive. The project was completed using a non-amine product. For 2025, the use of amine-based liquid anti-stripping asphalt additives will not be permitted on RIM projects.

3. Nova Scotia Department of Public Works (NSDPW) Contract Specifications

To avoid premature failure of the asphalt pavement surface due to stripping, NSDPW Contract Specifications have been written to require contractors to have their asphalt mix tested using a the Modified Lottman Test and a visual (laboratory) observation of the interior surfaces of artificially aged samples. Contract Specifications give options to contractors where the sample asphalt mix fails the Modified Lottman Test or visual observation.

When a sample asphalt mix fails the laboratory test or visual observation, there is no requirement to use a liquid anti-stripping asphalt additive. Instead, the contractor may choose to find another source of aggregate which does not strip or to use some other form of anti-stripping additive such as hydrated lime.

The Contract Specifications outline requirements to be met if the contractor decides to use a liquid anti-stripping asphalt additive.

For liquid additives that are based on amine chemistry, there are additional requirements to ensure healthy use. They include the requirement for the asphalt spreader (paver) to be equipped with a local exhaust ventilation system to capture and remove airborne vapours. Paving in damp weather conditions may require additional controls and paving in wet conditions is not permitted. Worker information sessions, provision of respiratory protection and relocation of sensitive workers away from further exposure are all covered by the specifications.

For 2025, the use of amine-based liquid anti-stripping asphalt additives will not be permitted on RIM projects.

4. Review of New Anti-Stripping Asphalt Additives

Having recognized the hazards associated with historic liquid anti-stripping asphalt additives, over the 30 years that additives have been used on Nova Scotia paving projects the chemical specialty industry has developed a number of new products. Initially these were principally less toxic amine-based products, some of which met the department's health screening criteria and were added to the list of "Acceptable" LAS additives.

Some of the new products were formulated using other chemistry that did not depend on amine-based chemicals. These were also reviewed for compliance with the department's health screening criteria and a number have been approved for use, providing options for contractors wishing to use a liquid anti-stripping asphalt additive that does not contain amines.

Over the last dozen years, there has been a move to more warm mix formulations. Some of these formulations use liquid anti-stripping asphalt additives, and if so, they must meet the same health screening criteria as the hot mix additives. In general, the amount of additive in warm mix formulations is lower than in hot mix formulations, and the lower temperatures used in warm mix formulations also reduces the amount of fume from the liquid asphalt cement and anti-stripping additive that get vaporized into the air.

5. Approval of Liquid Anti-Stripping Additives

Selection of liquid anti-stripping additives for use on Nova Scotia Department of Public Works projects starts with a review of the health and safety associated with their use, applying the following criteria:

A. For All Products

1. Administrative

- a. Available for sale in Canada
- b. All ingredient and specification information supplied as requested, including information which is regarded as trade secret or confidential business information (under a confidentiality agreement, if necessary)
- c. Complete and adequate Safety Data Sheet (SDS), meeting all Canadian Workplace Hazardous Materials Information System (WHMIS 2015) requirements. Note that this requirement also applies to any product that does not contain an ingredient that would normally trigger WHMIS classification criteria. Where all ingredient information is not fully disclosed (i.e.: listed as trade secret or confidential business information) the SDS must be reviewed by the Hazardous Materials Information Review Agency of Health Canada and must be issued with a Trade Secret Registry Number
- d. Sample of the formulation provided

2. Physical Characteristics

- a. Non-volatile formulation (no low boiling components)
- b. Low odour formulation

3. Toxicological Characteristics

- a. No ingredient with long term health effects, such as carcinogenicity, reproductive toxicity or lasting effect on any organ system
- b. No ingredient which is a primary lung sensitizing agent
- c. Overall formulation must be non-corrosive
- d. Overall formulation must be low irritant
- e. For formulations using a solvent to "cut" the final formulation, that solvent must be low toxicity

B. For Formulations Containing Amines

In addition to the criteria for approving all anti-stripping asphalt additives listed above, additional criteria are in place for evaluating amine-based formulations:

1. Additional Toxicological Characteristics

- a. No low molecular weight amines (e.g.: EDA, DETA, MEA) in final formulation
- b. No low molecular weight amines used as raw materials in preparing the formulation unless excess (unreacted amine) raw material is removed from the final formulation
- c. No primary amines in the final formulation
- d. Preference given to derivatized or substituted amines (e.g.: ethoxylated)

6. List of “Acceptable” Anti-Stripping Asphalt Hot Mix and Warm Mix Additives for 2025 NSDPW Projects

The products on this list have been subjected to an internal Occupational Health and Safety Review by NSDPW respecting their formulation and the toxicology of ingredients and have been determined to meet departmental criteria for use on 2025 paving projects. Inclusion on this list indicates that the product has been reviewed with respect to potential health effects on workers who may be exposed to it during asphalt hot or warm mix plant, spreading and compacting operations. Their use is governed by this 2025 Action Plan.

Product	Supplier	Maximum * Concentration
Additives that do NOT contain active amine compounds:		
Latex emulsion or polymeric treatment		
Ultracote	Ultrapave (Textile Rubber and Chemical Co. Affiliate)	
Organosilane compounds		
Zycosoil	Zydex	0.5%
Zycotherm	Zydex	0.5%
Zycotherm SP	Zydex	0.5%
Zycotherm SP2	Zydex	0.5%
Phosphate compounds		
CWM-P	Chemoran	0.75%
Evotherm P25	Ingevity	0.75%
Wetfix G400	Nouryon	0.5%
Additives that DO contain active amine compounds**:		
AD-here LOF 65-00	Arkema	0.5%
Evotherm M1	Ingevity	0.5%
Pave Bond Lite	Ingevity	1.0%

* Maximum concentration of liquid anti-stripping asphalt additive in hot or warm liquid asphalt cement, as delivered to the hot or warm mix plant. Addition at the asphalt plant is not allowed.

** Not permitted on RIM projects.

Please note that inclusion on this list does not mean that there will be no adverse effects associated with the use of the product, especially for amine-based anti-stripping additives. Worker exposure should be reduced as much as possible by careful consideration of site location, prevailing winds, moisture control, engineering controls, and other factors which can be controlled.

For amine-based products, more sensitive workers may experience some irritation of mucous membranes (especially mouth and upper respiratory tract) and may need to wear respiratory protective equipment. Workers who have been “sensitized” to the amine in these products may need to be removed from further exposure.

7. Approval of Asphalt Cement Suppliers

Liquid anti-stripping asphalt additives must be added at the refinery or tank farm. The additive may not be added at the hot or warm mix plant. To ensure that the proper additive in the correct amount is added, each supplier of asphalt cement wishing to provide liquid anti-stripping asphalt additive must submit a quality control program to NSDPW for review and approval.

The review ensures that proper equipment and procedures are in place for accurate addition of the liquid anti-stripping asphalt additive to the bulk asphalt cement transport tank(s) and that a current Safety Data Sheet meeting Canadian WHMIS 2015 standards is available from the supplier for the liquid asphalt cement which contains the anti-stripping product.

Each supplier chooses the liquid anti-stripping asphalt additives it will make available from the NSDPW List of “Acceptable” Additives. No supplier keeps all products on site, and it will be necessary for the paving contractor to discuss available products with their supplier of liquid asphalt cement.

8. Cooperation with Concerned Parties

Over the past 30 years, in the development and implementation of the LAS Action Plan, Nova Scotia Department of Public Works and its predecessor departments have worked closely with internal Joint Occupational Health and Safety Committees; the Nova Scotia Road Builders Association; suppliers of liquid anti-stripping asphalt additives; liquid asphalt cement suppliers (refineries and bulk distributors); hot and warm mix truckers; the Occupational Health and Safety Division of Nova Scotia Labour, Skills and Immigration and its predecessor departments; and safety organizations.

9. 2025 Action Plan

Based on the 1994 to 2024 experience, this 2025 Action Plan has been developed. Please note that this version of the plan is current as of the date noted at the bottom of the page. However, the plan is subject to change and NSDPW officials should be consulted to determine whether the plan has since been updated. A new Action Plan is produced each year, and only the Action Plan for the current year should be used. A free copy of the current Action Plan may be obtained using the contact information on the last page of this document.

For 2025, the significant change is that the use of amine-based liquid anti-stripping asphalt additives will not be permitted on RIM projects.

10. Pre-Construction Meeting

Each NSDPW project using a liquid anti-stripping asphalt additive must have a Pre-Construction Meeting between NSDPW officials and the contractor for that project to review the requirements for use of the additive in this 2025 Action Plan and the following three documents:

- Standard Specification for Highway Construction and Maintenance;
- Provisions for Use of Liquid Anti-Stripping Asphalt Additives on 2025 NSDPW Projects; and
- 2025 Check List for Liquid Anti-Stripping (LAS) Asphalt Additive Projects.

Items to be discussed also include equipment specifications, site-specific safety plan, safe work practices, use of protective equipment and worker information sessions. The responsibilities of NSDPW, the contractor and any other parties must be clearly defined.

For projects using an amine-based liquid anti-stripping asphalt additive, additional items must be discussed, including respiratory protection and protection of sensitive workers. For these projects, On-Site Representatives of the department and the contractor must be identified and their authority to act with respect to any on-site project contingencies must be established.

11. Site-Specific Safety Plan and Project-Specific Safe Work Practices

In advance of work starting, a Site-Specific Safety Plan must be developed, including Project-Specific Safe Work Practices to use in working with liquid asphalt cement or hot or warm asphalt mix which contains a liquid anti-stripping additive. The Project-Specific Safe Work Practices must be included in the Information Session for each group of workers. The Site-Specific Safety Plan and Safe Work Practices must:

- identify the proper location of the hot or warm mix plant in relation to the layout of the pit, quarry or other location where it is to be set up, taking into consideration the direction of prevailing winds;
- include the importance of avoiding contact with the hot or warm liquid asphalt cement or hot or warm asphalt mix containing liquid anti-stripping asphalt additive through the wearing of boots, long pants and a shirt to protect the skin. Natural fibre, such as cotton, wool, hemp, jute, linen, etc., is preferable to synthetics, such as nylon, polyester, rayon, etc., when protecting from the hazard from hot materials;
- include the importance of avoiding excessive breathing of the vapours from materials containing liquid anti-stripping additive by standing up wind to avoid exposure to vapour where possible, and by the use of respiratory protective equipment where necessary; and
- identify tasks where exposure to vapours from the liquid asphalt cement containing amine-based liquid anti-stripping additive could be high and will therefore require the mandatory use of respiratory protective equipment. For example, unless there is a local exhaust ventilation system installed to capture any vapours released, when a

worker must open a hatch on a hot or warm liquid asphalt cement storage tank, transport tanker or other vessel, they must wear full face respiratory protective equipment with organic vapour cartridges and dust pre-filters.

- include the requirement for asphalt spreaders (pavers) used on amine-based liquid anti-stripping projects to be equipped with local exhaust ventilation designed to capture and discharge fumes and vapours generated during the lay-down operation;
- for projects using an amine-based liquid anti-stripping additive, include the actions to be taken in various moisture conditions, such as:
 - delaying the start of paving until any standing water has drained or been removed from the road surface and the road surface is dry;
 - delaying the start of paving until morning fog has lifted and dew on the road surface has evaporated and the road surface is dry;
 - requiring the use of half-face respiratory protection during any short period of ground level fog or mist during the day; and
 - stopping paving operations at any time that it starts to rain. Tarpaulins should be placed over any trucks containing hot or warm mix. If the rain stops within 15 minutes, paving may resume once the road surface has dried. If the rain continues for more than 15 minutes, paving should cease until dry conditions return and the trucks containing hot or warm mix should be instructed to dump their loads at an approved disposal site.

Note that Model Safe Work Practices for Hot or Warm Mix Plants, for Paving Sites and for Hot or Warm Mix Truckers are available from NSDPW to assist in the development of the Site-Specific Safety Plan and Project-Specific Safe Work Practices.

12. Worker Information Sessions

Worker information is a critical part of the 2025 Action Plan. Worker Information Sessions are designed to provide up-to-date, reliable information to all present at the project. All supervisors and workers, including liquid asphalt cement carriers, asphalt hot or warm mix plant crews, asphalt concrete (hot or warm mix) truckers, paving crews, NSDPW project engineers, inspectors, checkers, consultants, etc., must be given a copy of the 2025 Action Plan and a formal Worker Information Session or a Refresher Session in advance of starting work.

The Worker Information Session (or Refresher Session) must include a review of the 2025 LAS Action Plan. Each worker should be given a copy of the 2025 LAS Action Plan. When the session is for a specific project, the liquid anti-stripping asphalt additive which will be used should be identified and the current Safety Data Sheet (SDS) for the hot or warm liquid asphalt containing the liquid anti-stripping asphalt additive must be reviewed. When the session is of a “general” nature, covering a number of projects where differing additives will be used, the session should review SDSs in general, noting the requirement to have a current SDS for the

actual product being used present for each project. Proper procedures to follow, use of protective equipment, reporting of illness, etc., all need to be covered.

Workers do not need to repeat the Worker Information Session for each new project or for each new paving season. Workers who have attended previous Worker Information Sessions do not need to attend the current session, but must be given a copy of the 2025 Action Plan and be informed in a Refresher Session of any changes to on-site procedures and the location of the current Safety Data Sheet.

13. Protective Clothing and Personal Protective Equipment

Using protective clothing and personal protective equipment (PPE) is a proactive approach which works together with engineering controls and safe work practices to prevent or reduce exposure to a hazard. Sometimes the use of protective clothing is just good safety practice and sometimes it is required by OHS regulations. Use of PPE can stop problems from developing where additional protection is required.

For LAS additives, protective clothing and PPE may act as a barrier between the person and the toxic chemical, keeping workers from being affected by the product or allowing workers who are sensitive to the product to continue working with it.

- Skin protection is primarily to prevent contact with hot mix, thus preventing thermal burns—no short pants, cut-offs or bathing suits.
- Shirts should cover the trunk of the body—no net shirts or tank tops. Long sleeves provide better protection, but in hot weather, short sleeves or no sleeves are reasonable accommodation.
- Safety boots should be laced up to prevent hot mix from getting inside the boot.
- For any operations which are not inside an enclosed vehicle, trailer, or building, a hard hat must be worn.
- Removing Asphalt Containing LAS Additive from Clothing—Treat asphalt hot mix or warm mix cement containing liquid anti-stripping asphalt additive the same as any other asphalt cement. Boots, gloves and clothing contaminated with asphalt cement that contains anti-stripping additive do NOT need to be discarded. They should be stored and cleaned the same as those contaminated with ordinary asphalt cement.
- Eyes—safety glasses are required when outside. They may be tinted safety glasses to protect the eyes from the sun.
- Nose, throat, lungs—Respiratory Protective Equipment (RPE), which also protects the eyes when “full-face” RPE is worn. For hot or warm asphalt mixes containing a non-amine based liquid anti-stripping asphalt additive, respiratory protection will not usually be needed, but projects using amine-based additives must be prepared for the potential need for respiratory protective equipment (see section 15).

14. Removing Asphalt Containing LAS from Skin

If your skin gets soiled from contact with hot or warm mix containing LAS additive, do not panic. The main hazard is thermal burns from the heat of the hot or warm asphalt mix. Give first aid for any thermal burns and seek medical attention if the burn needs cleaning.

If the skin is not burned, use soap or commercial hand cleaner to gently remove the tarry asphalt from the skin. This is all that is required.

15. Respiratory Protective Equipment (RPE)

The Respiratory Protective Equipment (RPE) which is required must be provided without cost to any workers who are performing tasks where exposure to amine-based anti-stripping additive vapours could be high, to any workers who experience symptoms from exposure to the additive, and to any workers who request to use RPE on a voluntary basis. NSDPW will supply RPE to its employees and to its consultants. Contractors will supply RPE to their workers. Independent truckers must supply their own RPE.

Respiratory Protective Equipment must be selected for the specific circumstances in which it is to be used, and must meet the following specifications:

- all RPE, including replacement components, must be approved by the US National Institute of Occupational Safety and Health (NIOSH);
- when eye irritation is not a problem, the RPE may be of the “half-face” (covers only the nose and mouth) type;
- when eye irritation is a problem, the RPE must be of the “full-face” type to protect the eyes as well as respiratory system;
- when a worker may be directly exposed to concentrated vapours of hot or warm asphalt cement containing amine-based liquid anti-stripping additive, such as from the open hatch on a hot or warm asphalt cement storage tank, the RPE must be of the “full-face” type;
- a worker who only requires RPE for short or intermittent time periods, such as to avoid minor throat or lung irritation, must be provided with a standard air purifying “half-face” respirator;
- a worker who is not physically affected by the amine-based anti-stripping agent but finds its odour to be objectionable or who voluntarily wishes to try a respirator must be provided with a standard air purifying “half-face” respirator for as long as the worker wishes;
- when a worker requires RPE for continuous or extended time periods (such as might be required by a worker who has become sensitized to the amine-based anti-stripping additive), a Powered Air Purifying Respirator (PAPR) must be provided;

- the RPE must be equipped with organic vapour cartridges and dust pre-filters (or provide equivalent protection). Some users have found the combination organic vapour/acid gas cartridge and dust pre-filters also give acceptable results, but this combination may have a shorter service life;
- organic vapour cartridges or organic vapour/acid gas cartridges must be replaced whenever there is "break-through" (smell) of vapours into the mask.
- dust pre-filters must be replaced when they become visibly dirty or when the resistance to breathing becomes noticeable;
- for air purifying respiratory protection to work effectively, it is necessary for it to have a close seal with the face. Therefore, areas of the face where the respirator makes contact must be clean shaven;
- every worker who is required to use RPE of the "full-face" or PAPR types, or who must use a "half-face" respirator to protect against further exposure when symptoms have been experienced from exposure to the amine-based liquid anti-stripping agent or because of provisions of the Site-Specific Safety Plan or Safe Work Practices, must be given a qualitative or quantitative fit test to ensure that the respirator has an adequate fit; and
- qualitative or quantitative fit testing is not required for workers who do not need respiratory protection or who are not experiencing symptoms of exposure but who voluntarily use "half-face" respirators because of product odour or personal wishes.

16. Contingency System

The objective of the Contingency System is to have **"site-based" decision making for any problems which develop**, so that immediate and appropriate action can be taken. At all times when work is in progress, each project on which an amine-based liquid anti-stripping asphalt additive is used must have both a Contractor's On-Site Representative (Superintendent, Foreman, etc.) and a NSDPW On-Site Representative (Project Engineer, Operations Supervisor, Inspector, etc.) on site, each of whom is thoroughly oriented to deal with any problems. These representatives must be authorized to make decisions on behalf of the contractor and NSDPW respecting any health or safety issues that may arise during the project.

When it is necessary for the Contractor's On-Site Representative or the NSDPW On-Site Representative to leave the workplace, they must first identify an on-site person who is authorized to act on their behalf during their absence so there will be no delay in on-site decision making regarding any health or safety issues during the period of absence.

The identities of the Contractor's On-Site Representative and the NSDPW On-Site Representative, and the names of their delegates when they are absent from the workplace, must be made known to all workers on site.

17. Protecting the Sensitive Worker

A key part of the Action Plan for the use of amine-based liquid anti-stripping asphalt additives is to consider a series of progressive actions to be taken in the event that any worker is adversely affected by the vapours (nose, throat, or lung irritation, eye irritation, headache, etc.) or feels nauseated by the odour from liquid asphalt cement or asphalt concrete (hot or warm-mix) containing the amine-based liquid anti-stripping additive.

- The **first line of defence** has been to carefully evaluate a number of liquid anti-stripping asphalt additives and select only those which will be less likely to give rise to health effects in exposed workers. Specifically, products have been selected which have low odour, low irritant potential, and low volatility (are less likely to give off vapours to which workers could be exposed) and have no evidence of long term health effects. Coupled with this choice of products are engineering controls, a Site-Specific Safety Plan and Project-Specific Safe Work Practices which are designed to reduce exposure to the greatest extent possible.
- The **second line of defence**, if a worker has a reaction to vapours from the amine-based liquid anti-stripping asphalt additive (nose, throat, or lung irritation, eye irritation, nausea, headache, etc.), is to provide that worker with RPE (see section 15. Respiratory Protective Equipment for specifications). Whenever a worker has an adverse reaction to the amine-based liquid anti-stripping asphalt additive, the NSDPW On-Site Representative must be notified.
- Respiratory protective equipment must also be provided on request to any worker who finds the odour from the amine-based liquid anti-stripping asphalt additive to be objectionable or who wants the security of additional protection and who voluntarily wishes to wear RPE.
- The **third line of defence** is relocation of any affected worker. If the RPE does not provide sufficient protection to a worker, or a worker is unusually sensitive to the vapours of the amine-based liquid anti-stripping asphalt additive, they must be reassigned to work in an area where there is less exposure to the product and where the worker is not affected. Whenever a worker is relocated, the NSDPW On-Site Representative must be notified.
- Very occasionally, a worker may need to be relocated to another workplace altogether, where amine-based liquid anti-stripping asphalt additive is not being used. If it is necessary to relocate a worker to another workplace, or whenever a worker exercises their right to Refuse Unsafe Work, the NSDPW On-Site Representative must be notified, who must in turn notify NSDPW senior management and the HSE Division of NSDPW.
- Any time a worker is adversely affected by exposure to amine-based liquid anti-stripping additive and must seek medical attention, the NSDPW On-Site Representative must be notified, who must in turn notify NSDPW senior management and the HSE Division of NSDPW.

- No worker is to be financially penalized for being reassigned to work in another area with less exposure or for being relocated to another workplace where amine-based liquid anti-stripping additive is not being used. Therefore, pre-relocation wage rate must be maintained for contractor employees, NSDPW employees and consultants contracted to NSDPW. This financial protection does not apply to independent hot or warm mix truckers.

18. Further Information

This document does not contain all the detail required for a specific project. Additional information will be required:

- contractors must obtain from their liquid asphalt cement supplier (generally an oil refinery or bulk distributor) a copy of the Safety Data Sheet (SDS) for the modified liquid asphalt product to be used. This SDS must have information about the liquid asphalt cement containing the liquid anti-stripping additive being used in the concentration range being used (i.e.: typically, a SDS for a 0.1% to 0.5% concentration of the liquid anti-stripping additive in 99.5% to 99.9% liquid asphalt cement). Note that the SDS for the pure liquid anti-stripping asphalt additive will not be appropriate for paving operations;
- workers must have access to the SDS for the liquid asphalt cement containing the LAS additive.
- contractors must develop a Site-Specific Safety Plan and Project-Specific Safe Work Practices for each operation where a worker could be exposed to vapours from asphalt containing liquid anti-stripping asphalt additive and should ensure that all supervisors and workers are trained in these practices. Note that Model Safe Work Practices for Hot or Warm Mix Plants, for Paving Sites and for Hot or Warm Mix Truckers on projects using amine-based additives are available from NSDPW to assist in the development of the Site-Specific Safety Plan and Project-Specific Safe Work Practices;
- workers must be given information on the Site-Specific Safety Plan and Project-Specific Safe Work Practices;
- contractors may wish to consult the Nova Scotia Road Builders Association, the Nova Scotia Construction Safety Association, the Nova Scotia Trucking Safety Association or other expert sources for further information on health and safety programs and for advice on Safety Plans and Safe Work Practices; and
- contractors should consult with their safety equipment supplier respecting the selection, use, care and maintenance of Respiratory Protective Equipment; fit testing of RPE for workers who require it (see last two bullets of Section 15), and for other health and safety equipment.

19. Resource Materials

A Trainer's Package, including the 2025 Action Plan, a PowerPoint Presentation, speaking notes and background materials (such as Model Safe Work Practices, etc.) is available to assist in providing Worker Information Sessions based on this Action Plan.

All trainers must have attended a Train-the-Trainer session organized by NSDPW or its predecessor organizations, although it does not have to be a session held in 2025. Trainers who have not attended a Train-the-Trainer session may arrange for one through NSDPW. Refresher training for trainers who have previously attended a Train-the-Trainer session may also be arranged through NSDPW.

Trainers who have attended previous sessions who have not already received 2025 training materials should request these materials from NSDPW. Electronic copies sent by email will be provided at no cost. Hard copy materials or electronic copies on a CD, DVD or USB thumb drive will be provided at a minimal cost.

Nova Scotia Department of Public Works will be pleased to receive comments on this Action Plan and the associated documentation.

Requests for an updated Trainer's Package (for trainers with previous training), Train-the-Trainer Sessions (for new trainers or as a refresher for trainers with previous training) or comments on the Action Plan should be directed to:

Catherine MacLeod, CRSP, CHSC, NEBOSH

Health, Safety and Environment Manager

Nova Scotia Department of Public Works

1672 Granville Street, 5th Floor

PO Box 186, Halifax, NS B3J 2N2

Office: (902) 722-5085

Cell: (902) 476-9879

Fax: (902) 424-0570